

MATERIAL SAFETY DATA SHEET

PACIFIC ADHESIVES COMPANY

8670 23rd Avenue
Sacramento, CA 95826

(916) 383-1509

DIVISION: ADHESIVE

DATE: 5/00

SECTION I - IDENTIFICATION

PRODUCT NAME: EWG-2200

CHEMICAL FAMILY DESCRIPTION: Polyvinyl Acetate Emulsion

SECTION II - HAZARD INFORMATION

COMPONENT	CAS NUMBER	WT. %	TLV
PVAc	9003-20-7	45-55%	N/A
Total residual monomer		less than 0.4%	10 ppm

*** No toxic chemicals subject to the reporting requirements of SARA Title III, Section 313 (40 CFR 372) are present***

SECTION III - PROPERTY INFORMATION

Boiling Point (F°): 210	Specific Gravity (HOH = 1): 1.1
Typical Viscosity (cps): 2000-5000	Percent Volatile (WT.%, Water): 45%
Vapor Density (Air = 1): 0.9	Evaporation Rate (HOH = 1): 1
Solubility in Water: Dispersable	pH: 5.0-6.0
Appearance and Odor: Milky liquid, slight vinegar odor	
Volatile Organic Content (V.O.C.): less than 4 g/L	

SECTION IV - FIRE AND EXPLOSION HAZARD INFORMATION

Flash Point (method used): None

Flammable Limits: N/A

Extinguishing Media: Water; CO₂; chemical

Special Fire Fighting Procedures: Wear MESA/NIOSH approved self-contained apparatus

SECTION V - HEALTH HAZARD DATA

Effects of overexposure: TLV not established
First Aid Procedures: If product gets in eyes flush with water

SECTION VI - REACTIVITY DATA

Stability: Stable
Conditions to Avoid: None
Incompatibility (materials to avoid): None
Hazardous Polymerization: Will not occur
Hazardous Decomposition Product: CO₂; CO

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case Material is released or spilled:
Use Borax to coagulate or as absorbent.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Wear suitable NIOSH/MSHA approved respirator where exposure limits may be exceeded.
Ventilation: Local Exhaust
Protective Gloves: Rubber
Eye Protection: Yes

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken during Handling and Storage:
Store in cool areas above freezing temperature.

SECTION X - MISCELLANEOUS